alter aircraft, airframes, powerplants, propellers, or component parts thereof. The Administrator may prescribe operations specifications containing limitations that the Administrator determines necessary to comply with the airworthiness requirements of this chapter.

(b) A certificated foreign repair station may perform only the specific services and functions within the ratings and classes that are stated in its operations specifications.

[Doc. No. 25454, 53 FR 47376, Nov. 22, 1988]

§145.75 Personnel.

- (a) Each applicant for a foreign repair station certificate and rating, or for an additional rating, must provide enough personnel who are able to perform, supervise, and inspect the work for which he seeks a rating, with regard being given to its volume of work.
- (b) The supervisors and inspectors of each certificated foreign repair station must understand the regulations in this chapter, FAA airworthiness directives, and the maintenance and service instructions of the manufacturers of the articles to be worked on. However, they do not need airman certificates issued under this chapter and, along with the persons performing the work of the station, are not considered to be airmen within the meaning of section 101(7) of the Federal Aviation Act of 1958 (49 U.S.C. 1301) with respect to work performed in connection with their employment by the foreign repair station.
- (c) In cases where the persons engaged in supervision or final inspection are not certificated under this chapter or by the country in which the station is located, their qualifications are determined by the Administrator, based on their ability to meet the requirements of paragraph (a) of this section as shown by oral or practical test or any other method the Administrator elects
- (d) No person may be responsible for the supervision or final inspection of work on an aircraft of United States registry at a foreign repair station unless he can read, write, and understand English.

§145.77 General operating rules.

Each certificated foreign repair station shall comply with the operating rules prescribed in subpart B of this part, except for §§145.61 and 145.63, and has the privileges of a domestic repair station as provided in §145.51.

§145.79 Records and reports.

- (a) Each certificated foreign repair station shall maintain such records, and make such reports, with respect to United States registered aircraft, as the Administrator finds necessary, including those prescribed in paragraphs (b) and (c) of this section.
- (b) Each certificated foreign repair station shall keep a record of the maintenance and alteration it performs on United States registered aircraft, in enough detail to show the make, model, identification number, and serial number of the aircraft involved, and a description of the work. In a case of major repairs or major alterations. or both, it shall report on a form and in a manner prescribed by the Administrator, giving the original copy to the aircraft owner and sending a copy to the Administrator through the FAA office having jurisdiction over the station. However, if a major repair or alteration is made on a United States scheduled flag air carrier aircraft, the report may be made in the log or other record provided by the carrier for that purpose. Upon request, the station shall make all of its maintenance and alteration records available to the Administrator.
- (c) Each certificated foreign repair station shall, within 72 hours after it discovers any serious defect in, or other recurring unairworthy condition of, any aircraft, powerplant, propeller, or any component of any of them, that it works on under this part, report that defect or unairworthy condition to the Administrator.
- (d) The holder of a foreign repair station certificate that is also the holder of a Type Certificate (including a Supplemental Type Certificate), a Parts Manufacturer Approval (PMA), or a TSO authorization or that is the licensee of a Type Certificate need not report a failure, malfunction, or defect under this section if the failure, malfunction, or defect has been reported